

## Schlage C Keyway

**5 PIN** - 2,000 key changes available under a master key system

**6 PIN** - 4,000 key changes available under a master key system

### **OLYMPUS DEADBOLT LOCKS**

#### **Olympus 700SC (door) - Olympus 800SC (drawer)**

**Cabinet locks:** Provide **Olympus 700SC (door)** and **Olympus 800SC (drawer)** easily rekeyable cabinet locks such as manufactured by Olympus Lock, Inc. All locks to include: forwardly removable cylinders for rekeying without totally disassembling lock body. Furnish 2 keys per lock and bar or slotted strikes as required. Spacers to be provided as required for flush fit with outside face of casework material. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule. Locks will have passed ANSI Grade 1 cycle testing.

### **OLYMPUS CAM LOCK**

#### **Olympus 820SC**

**Cabinet locks:** Provide **Olympus 820SC (cam)** locks. Locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All locks will include easily removable cylinders for rekeying without totally disassembling lock body. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule. Furnish 2 keys per lock.

### **OLYMPUS CAM LOCK**

#### **Olympus 829R**

**Cabinet locks:** Provide **Olympus 829R** sliding door ratchet lock such as manufactured by Olympus Lock, Inc. All locks will include easily removable cylinders for rekeying. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule. Furnish 2 keys per lock.

### **OLYMPUS LATCH LOCK (DEAD LATCH)**

#### **Olympus 850SC (drawer)**

**Cabinet locks:** Provide **Olympus 850SC (drawer)** locks. Locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All drawer latch locks to provide a deadlocking function, forwardly removable cylinders for rekeying without totally disassembling lock body, and spacers as required for flush fit with outside face of casework material. Furnish 2 keys per lock and strikes as required. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

### **OLYMPUS LATCH LOCK (SPRING LATCH)**

#### **Olympus L78R / L78L (door) - L78V (drawer)**

**Cabinet locks:** Provide **Olympus L78 (door)** and **Olympus L78 (drawer)** latch locks. Locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All latch locks to provide: forwardly removable cylinders for rekeying without totally disassembling lock body. Locks shall provide for field reversible handings such that keyway will remain in the vertical position regardless of installation as a door or a drawer. Spacers to be provided for flush fit with outside face of casework material. Furnish 2 keys per lock and strikes as required. Locks shall be capable of being keyed alike, keyed different and/or master keyed per supplied schedule.

### **GENERAL SPECIFICATIONS**

All cabinet door, drawer, and sliding door locks shall be easily rekeyable such as manufactured by Olympus Lock, Inc. All locks will provide a set screw cylinder release system or speed-release cylinder removal system so easy access to the solid brass cylinder and cylinder housing can be gained by facility or locksmith personnel for servicing and rekeying. Only a similar patented system that provides working top slides for easy access to top springs and pins is acceptable. No crimping on top slides will be considered. Cylinder spacers will be provided to allow flush fit of lock cylinders on outside of cabinet

material. Finishes will be similar to BHMA standards for US3, US26D, and 10B. No painted finishes will be acceptable.

Note: Rekeyable cabinet locks must be capable of being rekeyed in 5 minutes or less when off the cabinet to qualify under this specification.